




NPN Silicon Epitaxial Planar Transistor




TO-220AB



TO-220F



TO-252



1.Base,2.Collector,3.Emitter

FEATURES

- High voltage
- High speed switching

APPLICATIONS

- ELECTRONIC TRANSFORMER
- SWITCH MODE POWER SUPPLY


RoHS
 COMPLIANT

MECHANICAL DATA

- **Case:** Molded plastic
- **Polarity:** As marked
- **Mounting Position:** Any
- **Molded Plastic:** UL Flammability Classification Rating 94V-0
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Solder bath temperature 275°C maximum,10s per JESD 22-B106




Maximum Ratings at Ta=25°C unless otherwise specified

Characteristics	Symbol	Value	Unit
Collector Base Voltage	V_{CBO}	100	V
Collector Emitter Voltage	V_{CEO}	100	V
Emitter Base Voltage	V_{EBO}	5	V
Collector Current	I_C	3	A
Collector Peak Current Superimposed on Rated Load (JEDEC method)	I_{CP}	10	A
Base Current Superimposed on Rated Load (JEDEC method)	I_B	0.5	A
Power Dissipation (Tc = 25 OC) Superimposed on Rated Load (JEDEC method)	P_{tot}	2	W
Operating Temperature Range	T_J	150	°C
Storage Temperature Range	T_{STG}	-55 to +150	°C




Electrical Characteristics(Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_{CE} = 4V$, $I_C = 3A$	h_{FE}	10	-	100	-
Collector Base Cutoff Current at $V_{CB} = 100V$	I_{CBO}	-	-	200	μA
Collector Emitter Cutoff Current at $V_{CE} = 100V$	I_{CEO}	-	-	200	μA
Emitter Base Cutoff Current at $V_{EB} = 5V$	I_{EBO}	-	-	1000	μA
Collector Emitter Saturation Voltage at $I_C = 3A$, $I_B = 0.375A$	$V_{CE(sat)}$	-	-	1.2	V
Base Emitter Saturation Voltage at $I_C = 3A$, $V_{CE} = 4V$	$V_{BE(sat)}$	-	-	1.8	V
Transition Frequency at $V_{CE}=10V$, $I_C=500mA$, $f=1MHZ$	f_T	3	-	-	MHZ
Turn-Off Time at $I_C = 5A$, $I_B = 0.5A$	t_{off}	-	-	1.1	μs


RATINGS AND CHARACTERISTIC CURVES



Package Outline Dimensions millimeters

TO-220AB

TO-220F

TO-252


Marking on the body









Ordering information

Part Number	Package	Unit Weight	Base Quantity	Delivery mode
D880	TO-220AB	0.07oz(1.96g)	50 pcs / tube	1000pcs/box 5000pcs/carton
D880	TO-220F	0.06oz(1.74g)	50 pcs / tube	1000pcs/box 5000pcs/carton
D880	TO-252	0.011oz(0.32g)	2500 pcs / reel	5000pcs/box 25000pcs/carton

Note: For Halogen Free molding compound, add "H" suffix to part number above.

packing instruction

PKG	最小包装	内盒	外箱
TO-220AB TO-220F			
	50pcs/管	1000pcs/盒	5000pcs/箱
TO-252			
	2500pcs/盘	5000pcs/盒	25000pcs/箱

Notice

1. All product,product specifications and data are subject to change without notice to improve.The right to explain is owned by LINGXUN electronics company.

2. Confirm that operation temperature is within the specified range described in the product specification. Avoid applying power exceeding normal rated power;

exceeding the power rating under steady-state loading condition may negatively affect product performance and reliability.

3. LINGXUN electronics shall not be in any way responsible or liable for failure induced under deviant condition from what is defined in this document.