



MAIN CHARACTERISTICS

I_D	8A
V_{DS}	1700V
$R_{DS(on)-typ}$ (@VGS=18V Tc=25°C)	560mΩ



TO-247

Features

- High Speed Switching with Low Capacitances
- High Blocking Voltage with Low RDS(on)
- Easy to parallel
- Simple to drive
- RoHS Compliant

Benefits

- Increased Power Density
- Faster Operating Frequency
- Reduction of Heat Sink Requirements
- Higher Efficiency
- Reduced EMI

Applications

- Power Factor Correction Modules
- Switch Mode Power Supplies
- DC-AC Inverters
- High Voltage DC/DC Converters

Product specification classification

Part Number	Package	Mode Name	Pack
LSC560M170B	TO-247	LSC560M170B	Tube

Maximum Ratings at Tc=25°C unless otherwise specified

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	1700	V
Gate-Source Voltage	V_{GS}	-8/+22	V
Recommended Operation Value	V_{GSop}	-4/+18	V
Continue Drain Current	I_D	8	A
Pulsed Drain Current (Note1)	I_{DM}	16	A
Power Dissipation	P_D	79	W
Operating Temperature Range	T_J	-40 to +175	°C
Storage Temperature Range	T_{STG}	-40 to +175	°C
Thermal Resistance, Junction to Case	$R_{\theta JC}$	1.89	°C/W
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	40	°C/W

Note1:Pulse test: 300 μ s pulse width, 2 % duty cycle

Electrical Characteristics at Tc=25°C unless otherwise specified

Parameter	Test Condition	Symbol	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$V_{GS} = 0 \text{ V}, I_D = 100 \mu\text{A}$	BV_{DSS}	1700	-	-	V
Drain-Source Leakage Current	$V_{DS} = 1700 \text{ V}, V_{GS} = 0 \text{ V}$	I_{DSS}	-	1	5	μA
Gate Leakage Current	$V_{GS} = 18 \text{ V}, V_{DS} = 0 \text{ V}$	I_{GSS}	-	-	250	nA
Gate-Source Threshold Voltage	$V_{DS} = V_{GS}, I_D = 0.5 \text{ mA}$	$V_{GS(th)}$	2	2.6	4	V
Drain-Source On-State Resistance	$V_{GS} = 18 \text{ V}, I_D = 2 \text{ A}$	$R_{DS(on)}$	-	560	700	m Ω
	$V_{GS} = 18 \text{ V}, I_D = 2 \text{ A}, T_J = 175^\circ\text{C}$		-	880	-	
Input Capacitance	$V_{GS} = 0 \text{ V}, V_{DS} = 1000 \text{ V}, f = 1 \text{ MHz}$	C_{iss}	-	294	-	pF
Output Capacitance		C_{oss}	-	20.5	-	pF
Reverse Transfer Capacitance		C_{rss}	-	3.2	-	pF
Total Gate Charge(Note2)	$I_D = 2 \text{ A}, V_{DD} = 1000 \text{ V}, V_{GS} = -4/+18 \text{ V}$	Q_G	-	20	-	nC
Gate to Source Charge(Note2)		Q_{GS}	-	4	-	nC
Gate to Drain Charge(Note2)		Q_{GD}	-	10	-	nC
Turn-on Delay Time(Note2)	$V_{DS} = 1000 \text{ V}, I_D = 2 \text{ A}, V_{GS} = -4/+18 \text{ V}, R_G = 2.5 \Omega$	$t_{d(ON)}$	-	11	-	ns
Rise Time(Note2)		t_r	-	12	-	ns
Turn-Off Delay Time(Note2)		$t_{d(OFF)}$	-	15	-	ns
Fall Time(Note2)		t_f	-	27	-	ns
Turn-on Switching Energy		E_{on}	-	56	-	μJ
Turn-off Switching Energy		E_{off}	-	15	-	μJ

Source-Drain Diode Characteristics at Ta=25°C unless otherwise specified

Parameter	Test Condition	Symbol	Min.	Typ.	Max.	Unit
Maximum Body-Diode Continuous Current		I_S	-	-	8	A
Maximum Body-Diode Pulsed Current(Note2)		I_{SM}	-	-	16	A
Drain-Source Diode Forward Voltage	$V_{GS} = -4\text{ V}$, $I_{SD} = 2\text{ A}$	V_{SD}	-	4.7	5.5	V
Reverse Recovery Time(Note2)	$I_{SD} = 2\text{ A}$, $V_R = 1000\text{ V}$, $dI_F / dt = 1100\text{ A}/\mu\text{s}$	t_{rr}	-	25	-	ns
Reverse Recovery Charge(Note2)		Q_{rr}	-	39	-	nC
Peak Reverse Recovery Current		I_{rrm}	-	3.5	-	A

Note2:Pulse test: 300 μs pulse width, 2 % duty cycle

RATINGS AND CHARACTERISTIC CURVES




Figure 1. Output Characteristics

$T_j = -40^\circ\text{C}$




Figure 2. Output Characteristics

$T_j = -25^\circ\text{C}$




Figure 3. Output Characteristics

$T_j = 175^\circ\text{C}$




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current For Various Temperatures




Figure 6. On-Resistance vs. Temperature For Various Gate Voltage

RATINGS AND CHARACTERISTIC CURVES




Figure 7. Transfer Characteristic for Various Junction Temperatures




Figure 8. Body Diode Characteristic $T_J=40^{\circ}\text{C}$




Figure 9. Body Diode Characteristic $T_J=25^{\circ}\text{C}$




Figure 10. Body Diode Characteristic $T_J=170^{\circ}\text{C}$




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristics

RATINGS AND CHARACTERISTIC CURVES




Figure 13. 3rd Quadrant Characteristic
 $T_j=40^{\circ}\text{C}$




Figure 15. 3rd Quadrant Characteristic
 $T_j=175^{\circ}\text{C}$




Figure 17. Capacitances vs. Drain-Source




Figure 14. 3rd Quadrant Characteristic
 $T_j=25^{\circ}\text{C}$




Figure 16. Output Capacitor Stored
Energy




Figure 18. Continuous Drain Current
Derating vs. Case Temperature

RATINGS AND CHARACTERISTIC CURVES




Figure 19. Maximum Power Dissipation Derating vs. Case Temperature




Figure 20. Transient Thermal Impedance




Figure 21. Clamped Inductive Switching Energy vs. Drain Current




Figure 22. Clamped Inductive Switching Energy vs. $R_{G(ext)}$




Figure 23. Switching Times vs. $R_{G(ext)}$






Figure 24. Safe Operating Area

Package Outline Dimensions millimeters


T0-247



Marking on the body



packing instruction

PKG	Minimal Package	Mini Box	Box
T0-247			
	30pcs/pdpe	600pcs/box	3000pcs/box

Notice

All product, product specifications and data are subject to change without notice to improve. The right to explain is owned by LINGXUN electronics company.

Confirm that operation temperature is within the specified range described in the product specification. Avoid applying power exceeding normal rated

power; exceeding the power rating under steady-state loading condition may negatively affect product performance and reliability.

LINGXUN electronics shall not be in any way responsible or liable for failure induced under deviant condition from what is defined in this document.

<http://www.lxmicro.com>

Revision History

Rev	Changes	Date
1.0	First version	2025-8-20