

MAIN CHARACTERISTICS

I_D	7A
V_{DSS}	700V
$R_{DS(on)-typ}$ (@ $V_{GS}=10V$)	1.47 Ω

FEATURES



- Fast Switching
- Low ON Resistance
- Low Gate Charge
- 100% Single Pulse avalanche energy Test

APPLICATIONS


- Power switch circuit of adaptor and charger.

MECHANICAL DATA


- Case: Molded plastic
- Mounting Position: Any
- Molded Plastic: UL Flammability Classification Rating 94V-0
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Solder bath temperature 275 $^{\circ}$ C maximum, 10s per JESD 22-B106




TO-220F




TO-220AB



TO-263



TO-252



TO-251

Product specification classification

Part Number	Package	Mode Name	Pack
CS7N70A1	TO-220AB	CS7N70A	Tube
CS7N70A2	TO-220F (0.5mm)	CS7N70A	Tube
CS7N70A3	TO-263	CS7N70A	Tube
CS7N70A3-R	TO-263	CS7N70A	Tape
CS7N70A4	TO-251	CS7N70A	Tube
CS7N70A5-R	TO-252	CS7N70A	Tape

Maximum Ratings at $T_c=25^{\circ}\text{C}$ unless otherwise specified

Characteristics	Symbol	Value			Unit
		220AB/263	220F	251/252	
Drain-Source Voltage	V_{DS}	700			V
Gate-Source Voltage	V_{GS}	± 30			V
Continue Drain Current	I_D	7			A
Pulsed Drain Current (Note1)	I_{DM}	28			A
Power Dissipation	P_D	100	35	100	W
Single Pulse Avalanche Energy (Note1)	E_{AS}	350			mJ
Operating Temperature Range	T_J	150			$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150			$^{\circ}\text{C}$
Thermal Resistance, Junction to Case	$R_{\theta JC}$	1.25	3.57	1.25	$^{\circ}\text{C/W}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	62.5	62.5	100	$^{\circ}\text{C/W}$

Note1:Pulse test: 300 μs pulse width, 2 % duty cycle

Electrical Characteristics at $T_c=25^{\circ}\text{C}$ unless otherwise specified







Characteristics	Test Condition	Symbol	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = 250\text{ }\mu\text{A}$	BV_{DSS}	700	715	-	V
Drain-Source Leakage Current	$V_{DS} = 700\text{ V}, V_{GS} = 0\text{ V}$	I_{DSS}	-	-	1	μA
Gate Leakage Current	$V_{GS} = \pm 30\text{ V}, V_{DS} = 0\text{ V}$	I_{GSS}	-	-	± 100	nA
Gate-Source Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	$V_{GS(th)}$	2	-	4	V
Drain-Source On-State Resistance	$V_{GS} = 10\text{ V}, I_D = 3.5\text{ A}$	$R_{DS(on)}$	-	1.47	1.84	Ω
Forward Transconductance	$V_{DS} = 15\text{ V}, I_D = 3.5\text{ A}$	g_{fs}	-	6.5	-	S
Input Capacitance	$V_{GS} = 0\text{ V}, V_{DS} = 2\text{ V}, f = 200\text{ KHz}$	C_{iss}	-	1334	-	pF
Output Capacitance		C_{oss}	-	92	-	pF
Reverse Transfer Capacitance		C_{rss}	-	5	-	pF
Turn-on Delay Time(Note2)	$I_D = 7\text{ A}, V_{DD} = 325\text{ V}, R_G = 10\Omega$	$t_{d(ON)}$	-	18	-	ns
Rise Time(Note2)		t_r	-	19	-	ns
Turn-Off Delay Time(Note2)		$t_{d(OFF)}$	-	39	-	ns
Fall Time(Note2)		t_f	-	18	-	ns
Total Gate Charge(Note2)	$I_D = 7\text{ A}, V_{DD} = 520\text{ V}, V_{GS} = 10\text{ V}$	Q_G	-	22	-	nC
Gate to Source Charge(Note2)		Q_{GS}	-	5	-	nC
Gate to Drain Charge(Note2)		Q_{GD}	-	9	-	nC

Source-Drain Diode Characteristics at $T_a=25^{\circ}\text{C}$ unless otherwise specified

Characteristics	Test Condition	Symbol	Min.	Typ.	Max.	Unit
Maximun Body-Diode Continuous Current		I_S	-	-	7	A
Maximun Body-Diode Pulsed Current(Note2)		I_{SM}	-	-	28	A
Drain-Source Diode Forward Voltage	$I_{SD} = 7\text{ A}$	V_{SD}	-	-	1.4	V
Reverse Recovery Time(Note2)	$I_{SD} = 7\text{ A}, V_{GS} = 0\text{ V}, dt = 100\text{ A}/\mu\text{s}$	t_{rr}	-	370	-	ns
Reverse Recovery Charge(Note2)		Q_{rr}	-	1.9	-	μC


Note2:Pulse test: 300 μs pulse width, 2 % duty cycle

RATINGS AND CHARACTERISTIC CURVES




Package Outline Dimensions millimeters


T0-220F




T0-220AB




T0-263




T0-252




T0-251



Marking on the body



packing instruction

PKG	最小包装	内盒	外箱
TO-220F TO-220AB TO-263			
	50pcs/管	1000pcs/盒	5000pcs/箱
TO-252			
	2500pcs/盘	5000pcs/盒	25000pcs/箱
TO-263-R			
	800pcs/盘	1600pcs/盒	8000pcs/箱
TO-251			
	80pcs/管	4000pcs/盒	24000pcs/箱

Notice

All product,product specifications and data are subject to change without notice to improve.The right to explain is owned by LINGXUN electronics company.

Confirm that operation temperature is within the specified range described in the product specification. Avoid applying poer exceeding normal ratedpoer; exceeding the power rating under steady-state loading condition may negatively affect product performance and reliability.

LINGXUN electronics shall not be in any way responsible or liable for failure induced under deviant condition from what is defined in this documentpoer; exceeding the power rating under steady-state loading condition may negatively affect product performance and reliability.